

Safe Encasement Systems **Equipment Recommendations**

SE-110 Penetrating-Stabilizer (primer) and SE-120 or SE-130 Protective-Skin Encasement materials are pre-screened at the factory and can be applied with brush, roller, or airless spray equipment.

NOTES:

- To prevent damage to the coatings when removing all plastic and masking tape, use a utility knife to first cut at the coating edges.
- The circulation of air helps water based material to dry more rapidly.

Equipment recommendations: Use brushes, short nap rollers, or airless piston-type spray equipment that is rated at 1.0 gallons per minute (minimum) @ 3000 psi pressure, such as made by:

Graco info Hot-line is 1-800-328—0211 and/or
SpeedFlo info Hot-line is 1-800-526-5362 (Titan Tool, Inc.).

Hose: 3/8 inch (9.53mm) in-side diameter (minimum)

Guns: Graco Silver or Golden Hydra-Mastic guns (or-equal)

Tips: Use Reverse-To-Clean Type Tips;

- for SE-110 use .017 to .025 size tips,
- for SE-120 use .021 to .025 size tips.

Cleanup: Use soapy warm water. Immediately wipe surfaces not to be coated to prevent drying. All SES products are environmentally safe, water-based, low or zero VOC materials. Follow label instructions and MSDS for SE-110, SE-120 and SE-130 (PDS and MSDS can be downloaded at www.safeencasement.com).

Notes: Under normal drying conditions, SE-Encasement materials develop their full System Performance Qualities, including strength and chemical resistance properties within 3 to 14 days following application.

Call or visit our web-site for FAQ's.

Disclaimer: SAFE Encasement Systems, a NV-Corporation, has reliable data that's based upon information from Independent-Laboratory & Field-Testing and analysis, all which we believe to be accurate and reliable. Since the conditions of use are beyond SES's Control, we can not guarantee or accept any liability resulting from the misuse of our Products and Systems.

SAFE Encasement Systems, 7860 Dana Point Court, Las Vegas, NV 89117-1927

Phone: (888) 277-8834 or (702) 360-6111 ~ Fax: (888) 277-8835 or (702) 360-5827

www.safeencasement.com