

MATERIAL SAFETY DATA SHEET		<p>SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the hazardous effects of normal products of combustion.</p>	<p>Floors may be slippery, use care to avoid falls. Flush final traces with water. Keep spills and cleaning run-off materials out of municipal sewers or open bodies of water.</p>
<p>MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (800) 424-9300 ADDRESS: 7860 Dana Point Court, Suite R Las Vegas, NV 89117-1927 Revised: April 2001 Information. Phone: (888) 277-8834</p>			
<i>SECTION I - PRODUCT ID.</i>		<i>SECTION V - REACTIVITY DATA</i>	<p>WASTE DISPOSAL METHOD: Disposal should be in accordance with Federal, state and local regulations for water-based coatings. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Incinerate the solids and contaminated diking material at a permitted facility, according to Federal, State and local regulations.</p> <p>PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: <i>KEEP FROM FREEZING.</i></p>
<p>PRODUCT NUMBER: SE-110-CI PRODUCT NAME: Penetrating-Stabilizer-CI (Primer with Corrosion Inhibitors) PRODUCT CLASS: Specialty Acrylic Primer Coating</p>		<p>STABILITY: Stable (slight ammonia odor). CONDITIONS TO AVOID: <i>Keep from freezing.</i> INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable. Hazardous Polymerization: Will not occur HAZARDOUS DECOMPOSITION OR BY PRODUCTS: Will not occur.</p>	
<i>SECTION II - HAZARDOUS INGREDIENTS</i>		<i>SECTION VI - HEALTH HAZARD DATA</i>	<i>SECTION VIII - CONTROL MEASURES.</i>
<p>None known at a hazardous level (slight ammonia odor, contains less than Windex Glass Cleaner). HMIS Hazard Ratings = 0 0 0 J This product contains no heavy metals or fibers.</p>		<p>EFFECTS OF OVEREXPOSURE: INHALATION: inhaled mist can cause head aches, nausea or irritation of the nose, throat and lungs. EYE CONTACT: slightly irritating to eyes. SKIN EXPOSURE: irritating to skin upon prolonged or repeated contact.</p>	<p>VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS.</p> <p>RESPIRATORY PROTECTION: Wear respirator (MSHA or NIOSH Approved or equal) ORGANIC VAPOR/PARTICULATE RESPIRATOR. in case of poor ventilation or exposure to spray mist, use NIOSH APPROVED Organic Vapor Mask.</p> <p>PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT.</p> <p>EYE PROTECTION: CHEMICAL SPLASH GOGGLES (ANSI 2-87.1) or EQUIVALENT.</p> <p>OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Showers and cleaning of clothes are recommended. Use approved clothing when working around asbestos or lead.</p>
<i>SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS</i>		<p>EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject.</p> <p>OTHER PRECAUTIONS: <i>DO NOT TAKE INTERNALLY.</i> <i>KEEP AWAY FROM CHILDREN.</i></p>	
<i>SECTION IV - FIRE & EXPLOSION HAZARD DATA</i>		<i>SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE</i>	<i>SECTION IX - REGULATORY INFO.</i>
<p>APPEARANCE: Milky white liquid (dries clear) BOILING POINT: 100°C (212°F) Specific Gravity: Greater than 1.0 (H₂O = 1.0) VAPOR PRESSURE: (mm Hg @ 20°C) = 18 VAPOR DENSITY: lighter than 1.0 EVAPORATIVE RATE: equal to water PERCENT VOLATILE (by volume) = 50 - 55%</p>		<p>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. wear skin, eye and Respiratory Protection during cleanup. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer to containers for recovery or disposal.</p>	<p>DOT PROPER SHIPPING NAME: Not Regulated. Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.</p>
<p>FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED. FLASH POINT - N/A LEL - N/A EXTINGUISHING MEDIA: N/A UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F. Polymer film can burn.</p>			
SE-110-msds (04-01)			