

MATERIAL SAFETY DATA SHEET		UNUSUAL FIRE & EXPLOSION HAZARDS: There is no evidence that this product is sensitive to physical shock or static discharge.	SECTION VII - PRECAUTIONS FOR SAFE. HANDLING AND USE.
MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (800) 424-9300 ADDRESS: 7860 Dana Point Court, Suite R, Las Vegas, NV 89117 Revised: July 2000. Information Phone: (888) 277-8834		SPECIAL FIRE FIGHTING PROCEDURES: Follow normal fire fighting procedures. Self-Contained breathing apparatus should be worn, especially in enclosed areas. Will not burn unless preheated.	STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: N/A
SECTION I - PRODUCT ID.		SECTION V - REACTIVITY DATA	SECTION VIII - CONTROL MEASURES.
PRODUCT NUMBER: SE-SAT PRODUCT NAME: SELF-ADHESIVE TAPE PRODUCT CLASS: Butyl Seam Tape.		STABILITY: Stable. CONDITIONS TO AVOID: <i>Keep from excessive heat.</i>	VENTILATION: Not needed. RESPIRATORY PROTECTION: Not needed. PROTECTIVE GLOVES: Cotton or other protective gloves. EYE PROTECTION: Glasses or goggles. OTHER PROTECTIVE EQUIPMENT AND MEASURES: Long sleeves and long trousers to prevent skin contact.
SECTION II - HAZARDOUS INGREDIENTS		INCOMPATIBILITY: Avoid strong acids or strong oxidizing agents Hazardous Polymerization: Will not occur. HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield a variety of compounds such as CO, CO2, simple hydrocarbons, acids, aldehydes, ketones.	SECTION IX - REGULATORY INFO.
None known at a hazardous level.		SECTION VI - HEALTH HAZARD DATA	DOT PROPER SHIPPING NAME: Not Regulated.
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS		EFFECTS OF OVEREXPOSURE: INHALATION: Inhalation very unlikely. EYE CONTACT: May cause mild mechanical irritation to eyes. SKIN EXPOSURE: May cause mild irritation to skin.	Follow all applicable OSHA and EPA regulations concerning work activities.
APPEARANCE: Polyester backed grey tacky tape. BOILING POINT: 314°F. Specific Gravity: 1.25 (H ₂ O = 1.0). VAPOR PRESSURE: N/A VAPOR DENSITY: N/A EVAPORATIVE RATE: N/A PERCENT VOLATILE (VOCs): N/A		EMERGENCY AND FIRST AID PROCEDURES: For inhalation: could create a blockage, get medical attention. For eye & skin contact: care should be taken in the removal of the adhesive. Get medical attention if too sensitive. For ingestion: Unlikely, but if ingested it could create a blockage. Get medical attention.	
SECTION IV - FIRE & EXPLOSION HAZARD DATA		OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.	
FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED. FLASH POINT – Non combustible. LEL - N/A HAZARDOUS COMBUSTION PRODUCTS: Carbon nonoxide and carbon dioxide. EXTINGUISHING MEDIA: Water, dry chemicals, foam, carbon dioxide.			

