



07560 Membrane / Acrylic Urethane Architectural Sealant

PDS SE-151 (01-2006)

1. PRODUCT NAME

**SE-151 - Acrylic Urethane
Architectural Sealant**
*Interior/Exterior grade, High
Performance Elastomeric Sealant,
50 Year Limited Warranty*

2. MANUFACTURER

SAFE ENCASUREMENT SYSTEMS
8689 W. Sahara Ave., Suite 160
Las Vegas, NV 89117-5871
Phone: (888) 277-8834
Fax: (888) 277-8835
www.SafeEncasement.com

3. PRODUCT DESCRIPTION

SE-151 is a high performance urethane acrylic architectural sealant specially formulated to provide the ultimate in adhesion and durability. SE-151 has the ability to perform equally with silicone and one-part urethanes in most applications.

ADHERES TO: WOOD, METAL, MASONRY, DRYWALL, PLASTER, GLASS, CONCRETE, MASONITE and CERAMIC TILE

IDEAL FOR SEALING

AROUND: DOORS, SIDING, STUCCO, WINDOWS, MOLDING, SINKS, FLASHING PIPES, COUNTERS, EIFS and HARDBOARD SIDING.

BENEFITS:

- ✓ Superior Adhesion
- ✓ Long Term Durability
- ✓ Excellent Flexibility Over Wide Temperature Range
- ✓ Paintable
- ✓ Vacuumized for optimum performance
- ✓ Safe and Easy to Use
- ✓ Clean-up is with Water

4. TECHNICAL DATA

ASTM D412 Elongation = 525%.
Mildew Protected*.
Color – White.
Contents – 10.3 Fluid Ounces
(304 mL) per cartridge.
Meets or exceeds the requirements of Federal Spec. TT-S-230C, Type II, Class A and ASTM C-920, Grade NS, Class 25.
Keep From Freezing Before Use.
KEEP OUT OF THE REACH OF CHILDREN.

APPLICATION:

- Cut nozzle at 45° angle. Apply with a standard caulking gun.
- Smooth bead with a moistened finger, brush or cloth.
- Joint width should not exceed ¾". If joint depth exceeds ½", use a foam backer rod.
- Clean up tools with soap and water.
- May be overcoated with SE-120 system, latex or oil base paint when cured (generally within 2 to 6 hours, depending on climatic conditions).
- Forms a durable, airtight seal to give water and weather protection.
- Coverage: 51 linear feet at 3/16" diameter bead.
- Surface must be clean, dry and free from dirt, dust, grease, oil, mildew, wax, loose paint and old caulking material. Prime surfaces with SE-110 before applying. Apply only when sealant and surface temperature are above 50°F (10°C).
- Do not apply when rain or freezing temperatures are expected.
- Cool temperatures and high humidity retard cure.
- Not for underwater use.

6. AVAILABILITY & COST

SAFE Encasement Products may be purchased nationally or locally. For more information call (888) 277-8834 or (702) 360-6111.

7. 50 YEAR LIMITED WARRANTY

If, when applied as directed, this material peels, cracks or separates within 50 years after application, it will be replaced without charge upon presentation of proof of purchase and the used cartridge. *This Limited Warranty applies only to residential use.* All damages, including consequential damage, and other remedies are excluded. No other warranties apply, including fitness for a particular purpose. Various warranties are available for specific Encasement Systems installed by trained Applicators.

8. MAINTENANCE

Periodic inspections of Encasement Systems help ensure extended performance and reduce costs.

9. TECHNICAL SERVICES

Additional information, product brochures and Guide Specifications are available from our Technical Sales Consultants.

10. FILING SERVICES

Additional product information is available upon request.

** A mildew-resisting compound has been incorporated into this product to make its dry film mildew resistant.*

