



07560 Membrane / Seam Tape

PDS SE-SAT (01-2006)

1. PRODUCT NAME

SE-SAT – SELF ADHESIVE TAPE

2. MANUFACTURER

SAFE ENCASUREMENT SYSTEMS

8689 W. Sahara Ave., Suite 160
Las Vegas, NV 89117-5871
Phone: (888) 277-8834
Fax: (888) 277-8835
www.SafeEncasement.com

3. PRODUCT DESCRIPTION

SE-SAT SELF ADHESIVE TAPE is a 4-inch wide, high tensile strength, polyester-reinforced, butyl rubber sealant tape. It is designed to maintain outstanding performance characteristics for many years, remaining flexible and well adhered.

SE-SAT is an excellent product for repairing and reinforcing damaged fiberglass insulation. First apply SE-110 Penetrating-Stabilizer (primer) and when dry, apply SE-SAT to repair cracks. For the most effective long-term performance, SE-SAT in air supply ducts should be top-coated with suitable materials like SE-120 Protective-Skin and SE-170 High Gloss Topcoat.

BENEFITS:

- ✓ **Extremely Easy to Apply**
- ✓ **Instant Adhesion**
- ✓ **Long-Term Durability**
- ✓ **Excellent Flexibility Over Wide Temperature Range**
- ✓ **Safe and Easy to Use**
- ✓ **Environmentally Friendly**

4. TECHNICAL DATA

Appearance – Grayish-white fabric with gray adhesive.

Bonding Time – Immediate aggressive grip, full bond in 24 hours.

Facing/Backing – Spun bond polyester fabric.

Adhesive – 20 mils gray elastomeric butyl rubber.

Packaging – 4-inch x 50-foot rolls, 12 rolls per case.

Operating Temperature (-10°F to +180°F).

Tensile Strength – 570 psi with 75% elongation.

Shelf life – 18 to 24 months.

Peel Strength – 5 lbs. Per linear inch.

5. INSTALLATION

- All surfaces must be clean, dry, and free of dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- SE-SAT may be applied by hand, first cut to the desired length. Next, peel off plastic release liner and press into place removing all buckles and bubbles.
- Apply at temperatures above 50°F and below 110°F.
- Apply only when weather conditions will permit drying before rain, dew or freezing temperatures.

6. AVAILABILITY & COST

SAFE Encasement Products may be purchased nationally or locally. For more information call (888) 277-8834 or (702) 360-6111.

7. WARRANTY

Various warranties are available for specific Encasement Systems installed by trained Applicators.

8. MAINTENANCE

Periodic inspections of Encasement Systems help ensure extended performance and reduce costs.

9. TECHNICAL SERVICES

Additional information, product brochures and Guide Specifications are available from our Technical Sales Consultants.

10. FILING SERVICES

Additional product information is available upon request.

