

MATERIAL SAFETY DATA SHEET		
<p>MFG. BY: SAFE ENCASEMENT SYSTEMS EMERGENCY CONTACT: (800) 424-9300 ADDRESS: 7860 Dana Point Court, Suite R, Las Vegas, NV 89117-1927 Revised: July 2000. Information Phone: (888) 277-8834</p>	<p>FLASH POINT: N/A LEL: N/A EXTINGUISHING MEDIA: N/A UNUSUAL FIRE & EXPLOSION HAZARDS: None. SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the effects of hazardous combustion byproducts.</p>	<p>OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.</p>
SECTION VII - SPILL OR LEAK PROCEDURES.		
<p>SECTION I - PRODUCT IDENTIFICATION. PRODUCT NUMBER: SE-IC Industrial Cleaner PRODUCT CLASS: Alcohol Ethoxylate/Sodium Sulfate</p>	<p>SECTION V - SAFE HANDLING & USE INFORMATION. RESPIRATORY PROTECTION: Wear respirator, MSHA or NIOSH APPROVED (or the equivalent) in confined areas. VENTILATION: Mechanical local exhaust ventilation at point of contaminant release. PROTECTIVE GLOVES: Plastic or Rubber. EYE PROTECTION: Chemical splash goggles (ANSI 2-87.1) or equivalent. Have eye bath and/or safety shower available.</p>	<p>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. Dike and contain with inert absorbent materials (sand, Earth, etc.). Transfer to containers for recovery or disposal. Floors may be slippery; use care to avoid falls. Flush final traces with water. Keep spills and cleaning run-off materials out of municipal sewers or open bodies of water.</p>
<p>SECTION II - PHYSICAL & CHEMICAL CHARACTERISTICS. APPEARANCE: Light blue liquid, soluble in water. ODOR: Bland. BOILING POINT: 220°F. SPECIFIC GRAVITY: 1.12 (water = 1.0). VAPOR PRESSURE: N/E VAPOR DENSITY: N/E EVAPORATIVE RATE: less than water. PERCENT VOLATILE (by volume): 18%.</p>		<p>WASTE DISPOSAL METHOD: Disposal should be in accordance with Federal, state and local regulations. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP MATERIAL BETWEEN 40°F and 120°F.</p>
<p>SECTION III - REACTIVITY DATA STABILITY: Stable. CONDITIONS TO AVOID: Keep Between 40°F and 120°F. INCOMPATIBILITY: Bleach & Strong Oxidizers. HAZARDOUS POLYMERIZATION: Will not occur. HAZARDOUS DECOMPOSITION PRODUCTS: N/A</p>	<p>SECTION VI - HEALTH HAZARD DATA. EFFECTS OF OVEREXPOSURE: INHALATION: May cause difficulty in breathing. EYE Exposure: Possibly slightly irritating to eyes with direct contact. SKIN EXPOSURE: Possible skin irritant with prolonged or repeated contact. EMERGENCY AND FIRST AID PROCEDURES: For <u>inhalation</u>, move subject to fresh air. For <u>eye and skin contact</u>, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. <u>Ingestion</u> - If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY.</p>	<p>SECTION VIII - CONTROL MEASURES. OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Use approved clothing when working around ACM or Lead-Based Paints. Follow all applicable OSHA and EPA regulations.</p>
<p>SECTION IV - FIRE & EXPLOSION HAZARD DATA. FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED.</p>		
		SE-IC-msds (07-00)