



07560 Membrane / Architectural Sealant 100% Acrylic

PDS SE-150 (03/15)

1. PRODUCT NAME

SE-150 - 100% Acrylic Sealant
(Architectural grade Trowelable Sealant – 100% Acrylic)
Elastomeric 100% Acrylic Caulk

2. MANUFACTURER

SAFE ENCASUREMENT SYSTEMS
7860 Dana Point Court, Unit R
Las Vegas, NV 89117-1927
Phone: 888/ 277-8834
FAX: 888/ 277-8835
www.safeencasement.com

3. PRODUCT DESCRIPTION

SE-150 is a premium quality, water-based, elastomeric acrylic architectural sealant. It is designed to maintain outstanding performance characteristics for many years, remaining flexible, weather resistant, and well adhered.

SE-150 is an excellent product for filling holes or cracks in wood, masonry, asphalt roofing materials, sprayed polyurethane foam (SPF) roofing, single plies or around joints and flashiness.

SE-150 can be applied at temperatures between 50°F to 100°F.

BENEFITS:

- ✓ *Superior Adhesion*
- ✓ *Long-Term Durability*
- ✓ *Excellent Flexibility Over Wide Temperature Range*
- ✓ *Non Flammable*
- ✓ *No Solvents*
- ✓ *Safe and Easy to Use*
- ✓ *Environmentally Friendly*
- ✓ *Clean-up is with Water*

4. TECHNICAL DATA

ASTM D412 Elongation = 1150%.
ASTM C661 Shore A Hardness = 17
Colors – White, off-white or grey.
Solids by Volume = 60%.
Flexibility – passes 1 inch mandrel bend @ -15°F.

Weight – 8.8 pounds per gallon
ASTM C-920-79, Class 25 - Meets or Exceeds TT-S-00230C, Type II, Class A.

5. INSTALLATION

- May be applied by trowel, putty knife or caulking gun.
- All surfaces must be clean, dry, and free of dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- If the depth of a joint exceeds ½ inch, use a dry, non-asphaltic back-up filler material.
- Before curing, excess caulk can be removed with a damp cloth. After curing, it may be cut or scraped away.
- Apply at temperatures above 50°F. It's glove-able, easy to apply and use for repairs.
- Apply only when weather conditions will permit drying before rain, dew or freezing temperatures.
- Cool temperatures and high humidity retard cure.
- For application details see specific Guide Specifications.

6. AVAILABILITY & COST

SAFE Encasement Products may be purchased nationally or locally. For more information call 888/ 277-8834 or (702) 360-6111.

7. WARRANTY

Various warranties are available for specific Encasement Systems installed by trained Applicators.

8. MAINTENANCE

Periodic inspections of Encasement Systems help ensure extended performance and reduce costs.

9. TECHNICAL SERVICES

Additional information, product brochures and Guide Specifications are available from our Technical Consultants.

10. FILING SERVICES

Additional product information is available upon request.

