



07560 Membrane / Polyester Fabric

PDS SE-PF (01-2006)

1. PRODUCT NAME

SE-PF POLYESTER FABRIC,
Polyester Reinforcement Fabric

2. MANUFACTURER

TIETEX CORPORATION
P.O. BOX 6218
SPARTANBURG, SC 29304
PHONE: (803) 574-0500

Distributed By:

SAFE ENCASUREMENT SYSTEMS
8689 W. Sahara Ave., Suite 160
Las Vegas, NV 89117-5871
Phone: (888) 277-8834
Fax: (888) 277-8835
www.SafeEncasement.com

3. PRODUCT DESCRIPTION

SE-PF is a 100% polyester fabric made without the use of adhesives or binders. It is produced by the world's largest manufacturer of stitchbonded fabrics using state-of-the-art technology. The outstanding physical strength properties, quick wet-out and saturation characteristics, unique elongation features and ease of handling and application make it the best quality polyester fabric available for use with Elastomeric coating materials.

BENEFITS:

- **Adds Superior Reinforcement and Strength to Encasement Systems.**
- **Saturates Very Quickly.**
- **Long-Term Durability.**
- **Easy to Install.**
- **Environmentally Friendly.**

4. TECHNICAL PROPERTIES

Roll Dimensions:

- ✓ 20-inches wide x 324-foot long,
or
- ✓ 4-inches wide x 324 foot long.

Roll Sizes:

- ✓ 539 square foot, or
- ✓ 107 square foot.

Roll Weight:

- ✓ About 12 pounds, or
- ✓ About 2.4 pounds.

Weight - 3 ounces per square yard.

Bursting Strength - 177 pounds
tested by ASTM D3786.

Tensile Strength - 57.1 lb. per inch
(average, length & width)
tested by ASTM D1682.

Tear strength - 16.1 lb. (average,
length & width) tested by
ASTM D1117.

Elongation - 62% average (length
and width) tested by
ASTM D1682

Moldability - Excellent.

Ease of Saturation - Excellent.

5. INSTALLATION

- May be applied by hand or broom.
- All surfaces must be clean, dry, and free of dirt, grease, oil, or other contaminants that would interfere with proper adhesion.
- Complete saturation of the polyester fabric using SE-110 Penetrating-Stabilizer (primer) or SE-120 Protective-Skin topcoat materials.
- Apply at temperatures above 50°F.

- Apply only when weather conditions will permit drying before rain, dew or freezing temperatures.
- For application details see specific Guide Specifications.

6. AVAILABILITY & COST

SAFE Encasement Products may be purchased nationally or locally. For more information call (888) 277-8834 or (702) 360-6111.

7. WARRANTY

Various warranties are available for specific Encasement Systems installed by trained Applicators.

8. MAINTENANCE

Periodic inspections of Encasement Systems help ensure extended performance and reduce costs.

9. TECHNICAL SERVICES

Additional information, product brochures and Guide Specifications are available from our Technical Sales Consultants.

10. FILING SERVICES

Additional product information is available upon request.

